

Dynamic 2100

HD 2in1

Battery Powered
Strapping Tool
for plastic strapping



Versatile, Powerfull & Robust
*For a wide range of applications,
in all kinds of industries*

Dynamic 2100

Characteristics

- Strap qualities PET (Polyester) & PP (Polypropylene) plain or embossed
- Strap dimensions
 - Width 12,7 - 19,0 mm / 1/2 - 3/4"
 - Thickness 0,40 - 1,27 mm / .016 - .050"
- Tool weight 4,3 kg / 9.5 lbs
- Seal efficiency ~ 75 % of the strap break strength
- Seal method Friction
- Tensioning force 650 - 3.000 N / 146 - 675 lbs , adjustable
- Tensioning speed 160 - 230 mm/s / 6.3 - 9 inch/sec.
- Power source Li-Ion Battery 14,4 VDC / 3 Ah

Advantages

- Light weight, versatile strapping tool
- Robust and durable design
- Well proven strapping technology
- Simple 1-hand operation
- Excellent Cost / Performance Ratio
- Modern HQ Li-Ion battery technology



Item No.	Model	Strap width		Strap thickness	
		mm	inch	mm	inch
43.3291	Dynamic 2100 - 12,7/0,40-0,64	12,7	1/2"	0,40-0,64	.016-.025
43.3292	Dynamic 2100 - 12,7/0,65-1,05	12,7	1/2"	0,65-1,05	.026-.041
43.3301	Dynamic 2100 - 13/0,40-0,64	13		0,40-0,64	.016-.025
43.3302	Dynamic 2100 - 13/0,65-1,05	13		0,65-1,05	.026-.041
43.3311	Dynamic 2100 - 16/0,40-0,64	16,0	5/8"	0,40-0,64	.016-.025
43.3312	Dynamic 2100 - 16/0,65-1,05	16,0	5/8"	0,65-1,05	.026-.041
43.3322	Dynamic 2100 - 19/0,65-1,05	19,0	3/4"	0,65-1,05	.026-.041
43.3323	Dynamic 2100 - 19/1,06-1,27	19,0	3/4"	1,06-1,27	.042-.050

Your Dynamic distributor

